



MSDS

Material Safety Data Sheet

DATE PREPARED: 8/9/12

MANUFACTURER'S NAME: GARON PRODUCTS INC., PO Box 1924, Wall, NJ 07719-1924, 800-631-5380 FAX: 732-223-2002

EMERGENCY PHONE NO: CHEMTREC 800-424-9300

SECTION I – IDENTIFICATION

PART A

TRADE NAME: DECORPOXY™ KIT

PRODUCT CLASS:

PRODUCT CODE: 153814COLOR

DESCRIPTION: DECORATIVE EPOXY FLOOR RESURFACER

HAZARD RATING		
0 = Least	Health	2
1 = Slight	Flammability	1
2 = Moderate	Reactivity	0
3 = High	Personal Protection	
4 = Extreme		

HAZARDOUS COMPONENTS / CAS #	OSHA PEL	ACGIH TLV	OSHA STEL	WT%
Bisphenol A epoxy resin CAS# 25068-38-6	Not Established	Not Established		
Aliphatic Glycidyl Ether Diluent CAS# 68609-97-2	Not Established	Not Established		

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	>200°C (>392°F)	Specific Gravity (H ₂ O=1):	NA
Vapor Pressure:	<0.1kPa (<0.75 mm Hg) [20°C]	Density:	1.1 g/cm ³ [20°C(68°F)]
Vapor Density (Air=1):	NA	Evaporation Rate:	NA
Solubility in Water:	Practically Insoluble		
Appearance and Odor:	Colorless viscous liquid with slight odor.		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point:	485°F		Method Used:	Closed cup
Flammable Limits in Air by Volume:	UPPER:	NA	LOWER:	NA
Extinguishing Media:	Use water fog, alcohol foam, dry chemical or carbon dioxide.			
Special Firefighting Procedures:	Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure NIOSH approved self-contained breathing apparatus..			
Unusual Fire and Explosion Hazards:	Clear fire area of all non-emergency personnel. Cool fire exposed containers with water. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Material will not burn unless preheated. Combustion products may be toxic.			
Hazardous Thermal Decomposition Products	Carbon Dioxide, Carbon Monoxide, Halogenated Compounds			

SECTION V - REACTIVITY DATA

Stability	Stable. Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to Avoid	Avoid high temperatures. Excess heating over long periods of time degrades the resin. Avoid Heat, flames and sparks. Uncontrolled reaction with amines.
Incompatibility (Materials to avoid)	Can react vigorously with strong oxidizing agents, strong lewis or mineral acid, and strong mineral and organic bases, especially primary and secondary aliphatic amines. Reaction with some curing agents may produce considerable heat and possible violent decomposition.
Hazardous Decomposition or By-Products	Fire – Carbon Monoxide, Carbon Dioxide, Nitrogen Oxide, Aldehydes
Hazardous Polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.

MSDS**Material Safety Data Sheet**

DATE PREPARED: 8/9/12

SECTION VI - HEALTH HAZARD DATA A. Health risks and symptoms of exposure	
Inhalation	No known significant effects or critical hazards.
Skin Contact	Irritating to skin. May cause sensitization by skin contact.
Eye Contact	Irritating to eyes.
Ingestion	No known significant effects or critical hazards.

B. Health Hazards (Acute & Chronic): Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. WARNING! CAUSES EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. Do not breathe vapor or mist. Do not get on skin or clothing. Avoid contact with eyes. Wash thoroughly after handling.			
Medical Conditions Generally Aggravated by Exposure	Pre-existing skin disorders may be aggravated by over-exposure to this product.		
Carcinogenicity	OSHA: NO	NTP: NO	IARC: NO
No listed ingredients of this product are regulated as carcinogens. See health hazards acute and chronic for additional information concerning this product.			

C. Emergency & First Aid Procedures; Note to Physician: No specific treatment. Treat symptomatically. Call medical doctor or poison control center immediately if large quantities have been ingested. Persons with lung disorders or who are sensitized should not use this product.	
Eyes	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
Inhalation	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
Ingestion	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Never give anything by mouth to an unconscious person. Get medical attention immediately.

SECTION VII - SAFE HANDLING & USE INFORMATION	
Steps to be taken in case material is released or spilled	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
Waste Disposal Method	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Personal Precautions	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
Precautions to be taken in Handling and Storing	Avoid contact with skin, eyes and clothing. Avoid prolonged or repeated contact with skin, eyes and clothing. Wash thoroughly after handling. Heating this resin above 300°F in the presence of air may cause slow oxidative decomposition, above 500°F, polymerization may occur. Some curing agents, e.g., aliphatic polyamines, can produce exothermic reactions, which in large masses can cause runaway polymerization and charring of the reactants. Fumes and vapors from the thermal and chemical decompositions vary widely in composition and toxicity. Surfaces that are sufficiently hot may ignite even liquid product in the absence of sparks or flame. The resin may be handled, shipped and stored at elevated temperature in bulk. The recommended pumping temperature is 180°F. WARNING. Slightly toxic and may be harmful if absorbed through the skin. Causes skin irritation. May cause skin sensitization. Keep liquid and vapor away from heat, sparks and flame. Extinguish pilot lights, cigarettes and turns off all other sources of ignition prior to use and until all vapors are gone. Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Launder contaminated clothing before reuse. Contaminated leather articles, including shoes, cannot be decontaminated and should be destroyed to prevent reuse. Do not pressurize drum containers to empty them. To prevent thermal burns avoid contact with hot product. Containers, even those that have been emptied, can contain hazardous product residues. Store in a cool, dry place with adequate ventilation. Keep containers closed when not in use. Keep away from open flames and high temperatures.



MSDS
Material Safety Data Sheet
DATE PREPARED: 8/9/12

SECTION VIII - CONTROL MEASURES/PROTECTION INFORMATION	
Recommended Monitoring Procedures	Consult local authorities for acceptable exposure limits. If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
Engineering Measures	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Respiratory Protection	Use a NIOSH-approved respirator as required preventing overexposure. In accord with 29 CFR 1910.134, the types of respirator(s) to be considered include: Supplied-Air Respirator, Air-Purifying Respirator for Organic Vapors.
Ventilation	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Protective Gloves	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. >8 hours (breakthrough time): Polyvinyl Chloride (PVC), neoprene, nitrile rubber, Ethyl Vinyl Alcohol Laminate (EVAL), butyl rubber
Eye Protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Other Protective Clothing or Equipment	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Work / Hygienic Practices	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.



MSDS

Material Safety Data Sheet

DATE PREPARED: 8/9/12

MANUFACTURER'S NAME: GARON PRODUCTS INC., PO Box 1924, Wall, NJ 07719-1924, 800-631-5380 FAX: 732-223-2002

EMERGENCY PHONE NO: CHEMTREC 800-424-9300

SECTION I – IDENTIFICATION

PART B

TRADE NAME: DECORPOXY™ KIT

PRODUCT CLASS:

PRODUCT CODE: 153814COLOR

DESCRIPTION: DECORATIVE EPOXY FLOOR RESURFACER

HAZARD RATING	
0 = Least	Health
1 = Slight	Flammability
2 = Moderate	Reactivity
3 = High	Personal Protection
4 = Extreme	

HAZARDOUS COMPONENTS / CAS #	OSHA PEL	ACGIH TLV	OSHA STEL	WT %
Benzyl Alcohol CAS# 100-51-6	Not Established	Not Established	None	
N, Aminoethyl Piperazine CAS# 140-31-8	Not Established	Not Established	None	
Nonyl Phenol CAS# 84852-15-3	Not Established	Not Established	None	
Proprietary CAS# -----	T.S.C.A Status – OK on all above components			
Proprietary CAS# -----				
Proprietary CAS# -----				

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point or Range:	485°F	Specific Gravity (H ₂ O=1):	<1
Vapor Pressure (mm Hg):	.02	Melting Point:	N/A
Vapor Density (Air=1):	N/A	Evaporation Rate (Butyl Acetate=1):	N/A
Solubility in Water:	Partially Soluble		
Appearance and Odor:	Clear to Pale Yellow liquid with amine odor.		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point:	211°F		Method Used:	Closed cup
Flammable Limits in Air by Volume:	UPPER:	NA	LOWER:	NA
Extinguishing Media:	Foam, Alcohol Foam, CO ₂ , Water Fog			
Special Firefighting Procedures:	Do not enter confined space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure NIOSH approved self-contained breathing apparatus. Irritating gases may be generated.			
Unusual Fire and Explosion Hazards:	Cool exposed containers with cold water spray to prevent pressure build up that may rupture the container			

SECTION V - REACTIVITY DATA

Stability	Stable under normal use conditions.
Conditions to Avoid	Uncontrolled reaction with epoxy resins. Avoid breathing fumes generated by hardener and epoxy mixture when not used within established pot life.
Incompatibility (Materials to Avoid)	Can react vigorously with strong oxidizing agents, strong lewis or mineral acid, and strong mineral and organic bases, especially primary and secondary aliphatic amines.
Hazardous Decomposition or By-Products	By fire: Nitrogen, aldehydes, carbon monoxide and unidentified organic compounds may be formed during combustion.
Hazardous Polymerization	Hazardous polymerization will not occur.

MSDS**Material Safety Data Sheet****DATE PREPARED: 8/9/12**

SECTION VI - HEALTH HAZARD DATA A. Health risks and symptoms of exposure	
Inhalation	No known significant effects or critical hazards.
Skin Contact	Irritating to skin. May cause sensitization by skin contact.
Eye Contact	Irritating to eyes.
Ingestion	No known significant effects or critical hazards

B. Health Hazards (Acute & Chronic): Persons with lung disorders or who are sensitized should not use this product. ACUTE – Irritation on skin and dermatitis. CHRONIC – Repeated overexposure will cause severe skin irritation, dermatitis and sensitization. Sensitized persons may experience rapid irritation of skin upon exposure.			
Medical Conditions Generally Aggravated by Exposure	Allergies and skin disorders		
Carcinogenicity	OSHA: NO	NTP: NO	IARC: NO
No listed ingredients of this product are regulated as carcinogens. See health hazards acute and chronic for additional information concerning this product.			

C. Emergency & First Aid Procedures	
Eyes	Flush eye with water holding lids open for 15 minutes or more. Call physician for advice, if redness, burning, blurred vision or swelling persists.
Skin	Remove contaminated clothing. Promptly wash with soap and water. Do not use solvent. Flush with large amounts of water for at least 15 minutes. If persistent irritation occurs, obtain medical attention.
Inhalation	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.
Ingestion	Get medical attention immediately. Never give liquids to an unconscious person or convulsing person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Note: Persons with lung disorders or who are sensitized should not use this product.

SECTION VII - SAFE HANDLING & USE INFORMATION	
Personal Precautions	May burn although not readily ignitable. Prevent all bodily contact with spilled material. Wear protective equipment to prevent exposure. Shut off leaks, if possible without personal risk.
Steps to be taken in Case Material is Released or Spilled	Dike and contain. Contain run-off and dispose of properly. Prevent from entering into drains, ditches or rivers. Take up with an absorbent material and place in non-leaking containers. Seal tightly for proper disposal. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Wash area with detergent and water to remove trace residue.
Waste Disposal Method	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Precautions to be taken in Handling and Storing	Avoid contact with skin and eyes. Only use in well ventilated areas. Keep only in original container. Keep container tightly closed and in a cool, well-ventilated place. Keep container dry.

SECTION VIII - CONTROL MEASURES/PROTECTION INFORMATION	
Respiratory Protection	Use a NIOSH-approved respirator as required preventing overexposure.
Ventilation	Local Exhaust – If needed. Mechanical: Adequate exhaust ventilation must exhaust away from the applicator. Adequate ventilation to control airborne concentrations.
Protective Gloves	Impervious gloves, neoprene or rubber.
Eye Protection	Splash proof goggles or safety glasses with side shields. Eye wash fountains or an adequate supply of clean water must be available at the work site for emergency use.
Other Protective Clothing or Equipment	Avoid prolonged or repeated contact with skin. Wear other clothing as required minimizing contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams help when cleaning with soap and water. Use rubber apron, face shield, and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse.
Work / Hygienic Practices	Observe general good hygienic practices. Enforce careful handling to prevent splashing. Wash thoroughly after use.



MSDS

Material Safety Data Sheet

DATE PREPARED: 8/9/12

MANUFACTURER'S NAME: GARON PRODUCTS INC., PO Box 1924, Wall, NJ 07719-1924, 800-631-5380 FAX: 732-223-2002

EMERGENCY PHONE NO: CHEMTREC 800-424-9300

SECTION I – IDENTIFICATION

PART C

TRADE NAME: DECORPOXY™ KIT

PRODUCT CLASS:

PRODUCT CODE: 153814COLOR

DESCRIPTION: DECORATIVE EPOXY FLOOR RESURFACER

HAZARD RATING		
0 = Least	Health	0
1 = Slight	Flammability	0
2 = Moderate	Reactivity	0
3 = High	Personal	
4 = Extreme	Protection	

HAZARDOUS COMPONENTS / CAS #	OSHA PEL	ACGIH TLV	OSHA STEL	WT %
Silica Sand CAS# 14808-60-7	NA	.1MG/M ³	NA	94
Resin CAS# Non-Hazardous				4.95
TIO2 CAS# 13463-67-7				0.99
Inorganic Colorants CAS# Non-Hazardous				0.06

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point or Range	None	Evaporation Rate	NA
Vapor Density (Air=1)	None	Specific Gravity (H ₂ O=1)	2.65
Solubility in Water	Insoluble	Vapor Pressure	None
% Volatiles	<1%	PH	Inert
Appearance and Odor	Sand or aggregate, typical colors		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point	Non-Flammable	Method Used	
Flammable Limits in Air by Volume	UPPER:	NA	LOWER: NA
Extinguishing Media	Use extinguishing agents that are suitable to the surrounding fire; Water Spray, dry chemical, foam, or CO ₂ .		
Special Firefighting Procedures	This product is not combustible or flammable.		
Unusual Fire and Explosion Hazards	Products of combustion may include irritating gases.		

SECTION V - REACTIVITY DATA

Stability	Stable
Conditions to Avoid	Keep away from flames and excessive heats as this could cause the bag to ignite.
Incompatibility (Materials to avoid)	Dissolves in hydrofluoric acid.

SECTION VI - HEALTH HAZARD DATA A. Health risks and symptoms of exposure

Inhalation	NA
Skin Contact	NA
Eye Contact	NA
Skin Absorption	NA
Ingestion	NA



MSDS

Material Safety Data Sheet

DATE PREPARED: 8/9/12

B. Health Hazards (Acute & Chronic):

Medical Conditions Generally Aggravated by Exposure	Use of this product under normal and recommended conditions and specifications will pose no known hazards. However, if surfaces using this product are subjected to sanding or grinding as might occur for maintenance purposes and such treatment produces respirable dust, then proper ventilation and breathing apparatus should be used. Under such conditions, NIOSH-BOM approved respirators should be worn. Although these products are composed primarily of Silica Sand (SiO ₂), and such sand is potentially a source of respirable dust, the sand particles are thoroughly encapsulated in a coating which captures all dust and should, under normal circumstances, prevent any normal release of silica dust to the workplace.		
Carcinogenicity	OSHA: NO	NTP: NO	IARC: NO
No listed ingredients of this product are regulated as carcinogens. See health hazards acute and chronic for additional information.			

C. Emergency & First Aid Procedures

Eyes	Remove in same manner as one would remove any foreign particle. Get medical attention if irritation develops.
Skin	Wash with soap and water. Get medical attention if irritation develops.
Inhalation	Move from dusty area to fresh air and get medical attention for any breathing difficulty.
Ingestion	Swallowing this product is not recommended but should not cause harm.

SECTION VII - SAFE HANDLING & USE INFORMATION

Steps to be taken in case material is released or spilled	SMALL SPILL: If dust is generated, use appropriate respiratory protection. Vacuum or scoop material into an appropriately marked container for re-use or disposal. Avoid excessive generation of dust. LARGE SPILL: Use recommended protective clothing and respiratory protection. Use shovel to reclaim material. Vacuum or scoop material into an appropriately marked container for re-use or disposal. Avoid excessive generation of dust. It is more effective to clean this product while dry by vacuuming or sweeping. However, spill area can be washed with water. Collect wash water for approved disposal. Prevent runoff from entering storm sewers and ditches which lead to natural waterways.
Waste Disposal Method	Material which can not be reused should be disposed of in accordance with federal, state and local environmental control regulations at an authorized site by an approved contractor. Product and packaging can be disposed of or recycled as non-hazardous waste. Not a RCRA hazardous waste. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40CFR 261.20-24)
Precautions to be taken in Handling and Storing	Store dry at ambient temperature away from food and beverages, excessive heat or flame sources. Avoid breathing dust. Avoid getting in eyes or on skin. Wash hands thoroughly after handling. Avoid contact with moisture.



MSDS

Material Safety Data Sheet

DATE PREPARED: 8/9/12

SECTION VIII - CONTROL MEASURES/PROTECTION INFORMATION	
Respiratory Protection	Workplace ambient dust concentrations should be monitored and if the recommended exposure limit is exceeded, a NIOSH/MSHA approved respirator with dust pre-filter should be worn.
Ventilation	Maintain air levels below the recommended exposure limit using process enclosure and exhaust ventilation if necessary. Supply sufficient replacement air to make up for air removed by exhaust systems. If engineering controls and work practices are not effective in controlling exposures, appropriate personal protective equipment including a NIOSH/OSHA approved respirator should be worn.
Protective Gloves	Impervious gloves, neoprene or rubber or leather.
Eye Protection	Splash proof goggles or safety glasses with side shields. Eyewash stations should be available in the workplace.
Other Protective Clothing or Equipment	Educate and train employees in the safe use and handling of hazardous chemicals.
Work / Hygienic Practices	Observe general good hygienic practices. Wash hands and face before eating, drinking, or using tobacco products.

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material.